FLOOR MACHINES

Selectline® 13, 17 & 20

- Multipurpose 13", 17" and 20" machines
- 1.0 hp AC motor, 175 rpm
- Dual-planetary, all metal gears
- Pad holder included

SelectLine® 20TS

- 20" two-speed floor machine
- 1.5 hp DC Rectified motor
- 180/320 rpm
- Triple planetary gears
- Pad holder included

SelectLine® 17HD & 20HD

- Multipurpose 17" and 20" machines
- 1.5 hp AC motor, 175 rpm
- Triple planetary gears
- Pad holder included

ECFM 17 & 20

- Available in 17"and 20" models
- 1.0 hp AC motor
- 175 rpm
- Pad holder included

Models:	ECFM 17	ECFM 20	SelectLine® 20TS	SelectLine® 13
Brush Diameter:	17 in (43 cm)	20 in (51 cm)	20 in (51 cm)	13 in (33 cm)
Frame Size:	66	66	66	66
Motor:	1 hp	1.5 hp	1.5 hp rectified	1 hp
Capacitor(s):	Dual, start and run	Dual, start and run	—	Dual, start and run
Output Speed:	175 rpm	175 rpm	180/320 rpm	175 rpm
Transmission:	Dual planetary gears – all metal	Dual planetary gears – all metal	Triple planetary gears – all metal	Dual planetary gears – all metal
Clutch Plate:	NP 92 (industry standard)	NP 92 (industry standard)	NP 92 (industry standard)	NP 92 (industry standard)
Amp Rating:	12 A	13.5 A	15 A	12.6 A
Voltage/Frequency:	120 V/60 Hz	120 V/60 Hz	120 V/50-60 Hz	120 V/60 Hz
Noise Level:	65 dB A	65 dB A	70 dB A	65 dB A
Power Cord:	50 ft (15.25 m)	50 ft (15.25 m)	50 ft (15.25 m)	50 ft (15.25 m)
Weight:	90 lb (41 kg)	93 lb (42 kg)	87 lb (40 kg)	81 lb (37 kg)

Models:	SelectLine® 17	SelectLine® 20	SelectLine® 17HD	SelectLine® 20HD
Brush Diameter:	17 in (43 cm)	20 in (51 cm)	17 in (43 cm)	20 in (51 cm)
Frame Size:	66	66	66	66
Motor:	1 hp	1 hp	1.5 hp	1.5 hp
Capacitor(s):	Dual, start and run	Dual, start and run	Dual, start and run	Dual, start and run
Output Speed:	175 rpm	175 rpm	175 rpm	175 rpm
Transmission:	Dual planetary gears – all metal	Dual planetary gears – all metal	Triple planetary gears – all metal	Triple planetary gears – all metal
Clutch Plate:	NP 92 (industry standard)	NP 92 (industry standard)	NP 92 (industry standard)	NP 92 (industry standard)
Amp Rating:	12.6 A	12.6 A	15 A	15 A
Voltage/Frequency:	120 V/60 Hz	120 V/60 Hz	120 V/60 Hz	120 V/60 Hz
Noise Level:	65 dB A	65 dB A	65 dB A	65 dB A
Power Cord:	50 ft (15.25 m)	50 ft (15.25 m)	50 ft (15.25 m)	50 ft (15.25 m)
Weight:	90 lb (41 kg)	93 lb (42 kg)	100 lb (45 kg)	102 lb (46 kg)

KENT
Simple. Clean.

14600 21st Avenue North
Plymouth, Minnesota 55447-3408
www.kenteuroclean.com
Phone 800-545-4372
Fax 866-261-4779

240 Superior Boulevard
Mississauga, Ontario, Canada L5T 2L2
www.kenteuroclean.com
Phone 905-564-1149 or 800-668-8400
Fax 905-564-1030 or 800-263-5111

©2008 Kent is a registered trade name of Nilfisk-Advance, Inc. Form L1732K 8-08

recyclable